CE

BS EN 14351-1:2006+A2:2016

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

DECLARATION OF PERFORMANCE

THIS IS TO CERTIFY THAT

DEM WINDOW SYSTEMS LIMITED

34 / 35 GRANGE LANE INDUSTRIAL ESTATE, STAIRFOOT, BARNSLEY. S71 5AS

dem WINDOW SOLUTIONS

HAVE CONFORMED WITH EN 14351-1:2006 + A2:2016 ANNEX ZA

AVCP LEVEL 3

FOR

VEKA/WHS HALO UPVC WINDOWS & EXTERNAL DOORSETS

WINDOWS & DOORS INTENDED TO BE USED IN DOMESTIC AND COMMERCIAL LOCATIONS

INSTIGATING AND IMPLEMENTING A SYSTEM OF FACTORY PRODUCTION CONTROL COMPLYING WITH EN 14351-1:2006 + A2:2016 ANNEX ZA

PRODUCING A TECHNICAL FILE CONTAINING THE TEST REPORT AND PERFORMANCE INDICATION PAPERS FOR ALL COMPONENTS

INCLUDING THE FOLLOWING MANDATORY REQUIREMENTS

DANGEROUS SUBSTANCES - Clause 4.6

LOAD BEARING CAPACITY OF SAFETY DEVICES - Clause 4.8

THERMAL CHARACTERISTICS - Clause 4.12

Signed: D AIREY

Position: Production Director

Date: 31/07/19

CE

DEM WINDOW SOLUTIONS LIMITED

34 / 35 GRANGE LANE INDUSTRIAL ESTATE, STAIRFOOT, BARNSLEY. S71 5AS

13

EN 14351-1:2006 + A2:2016

AVCP LEVEL 3

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

WHS HALO/VEKA PVC WINDOW & DOOR PROFILE

Characteristics	Declared Value
Dangerous Substances	None
Thermal Transmittance	WINDOWS ≤ 1.6W/(m^2K),DOORS ≤ 1.8W/(m2K)
Load Bearing Capacity of Safety Devices	Passed
Resistance to Wind Load	NPD
Resistance to snow and permanent load	NPD
Reaction to fire	NPD
External Fire Performance	NPD
Water tightness	NPD
Impact Resistance	NPD
Radiation Properties	NPD
Acoustic Performance	NPD
Air Permeability	NPD
The Ability to Release	NPD

This declaration relates to a worst case scenario and as such all our products will give an equal to or better (lower) than performance to that quoted

Signed: D AIREY **Date:** 31/07/19

Position: Production Director